

2 Core Twisted Shielded Accelerometer Cable – One Side 2 Socket Circular MIL Connector Other side BNC



Product Specifications

2 Core Shielded Cable

Jacket Material	Grey PVC
Application	Permanent Monitoring
Conductor Quantity	2 Conductor
Cable Diameter	5.6mm
Shielding Method	Tinned Copper Braiding
Aluminum foil tape protection	For preventing signal losses
Mutual Capacitance	120nF/km
Temperature Range	-40°C to 80°C

MIL Connector

Application	Permanent Mount
Maximum Temperature	200°C
Connecting Type	2 Socket MIL
Operating Temperature	-55°C to 125°C
Durability	100 Cycles
Coupling Style	Threaded
Pinout	A: Signal B: Common

BNC Connector

Model	BNC Connector
Characteristic Impedance	50Ω
Body Material	Stainless Steel
Insulation Resistance	50x10 ⁶ ohm
Shell Material	Brass
Pin Contact	Gold Plated
Pin Out	Center Pin: Signal Shell: Common

Tyrannus Innovative Engineering & Research Academy Pvt. Ltd
TrEST Research Park
Ground Floor
TC- 4/2322, GEM building,
(Opp) College of Engineering Trivandrum
Engineering College PO, Kerala – 695016
sales@tieraonline.in

